

## monitor 19 LCD Monitor

### QBST.19NB

[P216200A - Cod. EAN 8032891991459]

#### 19" LCD monitor for video-security system.

Professional LCD monitor with VGA and DVI video connections and

Resistive Touch Screen panel suitable for interactive applications.



LCD PANEL	
LCD Type	Tv monitor LCD 19" active matrix anti glare
Dimension of the panel	19", 4:3
Touch screen	Five-Wire Resistive Panel, anti glare. Compatible with manual touch and/or pen
Viewing area	19" diagonal
Native Resolution	1280 x 1024
Contrast (DCR)	4000:1 (tip.)
Viewing Angle	175° O. (tip.), 170° V. (tip.) - CR >= 10:1
Response Time	2 ms (G to G)
Lights	Long lasting, 50.000 hours (tip.)
Brightness	350 cd/m <sup>2</sup> (tip.)
VIDEO INPUTS	
VGA	RGB analogic (75 ohm, 0.7 Vp-p), H Freq.: 30-64KHz; V Freq.: 60-75Hz, H/V separate (TTL)
DVI	Digital DVI-D input
CONTROLS	
Keyboard	Standby on/off, input selection, Channel +/-, Volume +/-, menu
OSD	Auto adjust, contrast, brightness, horizontal position, vertical position, phase, clock, picture size, color temperature, sound system
USB	
	USB digital input for the management of Touch Screen
PHP COMPATIBILITY	
Pc	up to 1280 x 1024 (native)
ABSOLUTE MAXIMUM RATINGS	
Temperature	0-40°C
Humidity	10-65% (without moisture)
CONNECTORS	
Analogic/Digital	D-sub (VGA) 15-pin, DVI-D
POWER SUPPLY	
Voltage operating range	External supplier 100 ~ 240 Vac / 50 ~ 60 Hz, Supplier 12 V DC, 5A
Consumption	< 45W (tip.), < 2W in StandBy
Connector	Italian Plug
DIMENSIONS (W X H X D) mm	
Dimensions	445 x 445 x 201
WEIGHT	
Net/Gross	5 / 6 Kg
VESA MOUNTING SYSTEM	
W x H mm	100 x 100
STANDARDS	
	CE, ISO 13406-2 Classe B, RoHS
RECYCLING	
	The lights contain mercury thus they have to be recycled according to law standards
ACCESSORIES	
	RCU with batteries, user's guide. Cables: power cord, VGA, RCA audio/video
WARRANTY	
	3 years warranty (ISO 13406-2 Class II)

